

**DECLARATION OF COMPLIANCE**

Description	Material	Article Number
Seal film	PET	162800

Duni declares that the article meets the requirements of:

- EU Regulation 1935/2004/EC (Framework regulation)
- EU Regulation 2023/2006/EC (GMP)
- EU Regulation 10/2011/EC with amendments (Plastic regulation)

**Overall migration (1)**

According to the above mentioned regulations, the overall migration does not exceed 10 mg/dm<sup>2</sup> or 60 mg/kg.

**Specific migration (2)**

This article contains monomers or additives subject to restrictions under the plastic regulation 10/2011 and its amendments. A specific migration test proves that these are within the limits. If more information regarding the monomers or additives are needed please contact Duni AB.

**Area of use**

Based on the migration tests and Declaration of Compliance, the articles can be used safely with all types of foodstuffs at any period at temperatures up to 40°C, 60 minutes at 100°C, 30 minutes at 210°C.

**Test conditions**

Migration tests on the material of the article performed by an independent institute showed that under the following test conditions overall migration (1) and specific migration (2) fall below the respective limits given by regulation 10/2011.

**Overall migration OM6\***

*3% Acetic Acid 4 hours at 100°C*

*10 % Ethanol 6 hours at 60°C*

*Vegetable oil 2 hours at 200°C*

*95% Ethanol 6 hours at 60°C*

*\*corresponding standard testing conditions in 10/2011*

**Specific migration**

*3% Acetic acid 4 hours 100°C*

The ratio of food contact surface area to volume used is 6 dm<sup>2</sup>/kg

Dual Additives that might be present in the product:

CAS No	Substance
10043-35-3	Boric acid (E284)
7665-38-2	Phosphoric acid ((E338)
128-37-0	Butylated hydroxytoluene (E321)
1338-43-8	Sorbitan monooleate (E494)

According to the document in our possession, Primary Aromatic Amines are below 10 PPb.

Please be advised that Duni Group does not add anything into the product.

Recommended storage conditions: 15°C-25°C (55°F-77°F) in a dry place, away from direct sunlight. Maximum storage time from point of unloading of goods to be 6 months, if stored as recommended.

This document of compliance is based on:

- Documentation from suppliers
- Overall migration test
- Specific migration

This document was issued electronically and is therefore valid without signature.