

DECLARATION OF COMPLIANCE

| Description | Material | Article Number |
|-------------|----------|----------------|
| Tray | PP | 758000 |

Duni declares that the article meets the requirements of:

- Article 3, 11(5), 15 and 17 of Regulation (EC) No 1935/2004 (Framework regulation) EU Regulation 2023/2006/EC (GMP)
- EU Regulation 2023/2006/EC (GMP)
- EU Regulation 10/2011/EC with amendments (Plastic regulation)

Overall migration (1)

According to the above mentioned regulations, the overall migration does not exceed 10 mg/dm² or 60 mg/kg.

Specific migration (2)

This article contains monomers or additives subject to restrictions under the plastic regulation 10/2011 and its amendments. A specific migration test proves that these are within the limits. If more information regarding the monomers or additives are needed please contact Duni AB.

Area of use

Based on the migration tests and Declaration of Compliance in Duni's possession, the articles can be used safely with all types of food in the microwave and under following conditions:

Temp (Time): +120°C (1h), +70°C (4h), +40°C (10days), -20°C (unlimited)

b120a4d6-3c9b-46d2-b298-54ae4b06ec5b

Test conditions

Migration tests on the material of the article performed by an independent institute showed that under the following test conditions overall migration (see 1.) and specific migration (see 2.) fall below the respective limits given by regulation 10/2011.

Overall migration

| | |
|----------------|-------------------------------|
| 10 % Ethanol | 2 hours at reflux temperature |
| 3% Acetic acid | 2 hours at reflux temperature |
| Olive oil | 1 hour at 121°C |

Specific migration

| | |
|----------------|-------------------------------|
| 10 % Ethanol | 2 hours at reflux temperature |
| 3% Acetic acid | 2 hours at reflux temperature |
| 95 % Ethanol | 4 hours at 60°C |
| Isooctane | 2 hours at 60°C |
| MPPO | 1 hour at 121°C |

Specific migration of metals

| | |
|----------------|-------------------------------|
| 3% Acetic acid | 2 hours at reflux temperature |
|----------------|-------------------------------|

Specific migration of PAA

| | |
|----------------|-------------------------------|
| 3% Acetic acid | 2 hours at reflux temperature |
|----------------|-------------------------------|

The ratio of food contact surface area to volume used is between 5-10 dm²/kg

No substances of dual use are present in the product.

The product does not contain any functional barrier.

Please be advised that Duni AB does not add anything into the product.

This document of compliance is based on:

- Documentation from suppliers
- Global migration test
- Specific migration

This document was issued electronically and is therefore valid without signature.